

# tesa® 4934

Double-sided fabric tape

## PRODUCT INFORMATION

### Product Description

tesa® 4934 is a double-sided tape. It consists of a fabric backing with a thick, tacky adhesive coating. The synthetic rubber adhesive is solvent free.

tesa® 4934 is a general purpose mounting tape.

tesa® 4934 is easily hand tearable.

### Main Application

Due to the flexible fabric backing and the high coating weight it is particularly suited for mounting on rough, fibrous surfaces, for example carpet laying.

### Technical Data

■ Backing material	cloth	■ Elongation at break	20 %
■ Colour	white	■ Tensile strength	35 N/cm
■ Total thickness	200 µm	■ Type of liner	glassine
■ Type of adhesive	synthetic rubber		

### Adhesion to

■ Steel (initial)	14.5 N/cm	■ Steel (after 14 days)	24.0 N/cm
■ PE (initial)	8.0 N/cm	■ PE (after 14 days)	8.5 N/cm
■ PP (initial)	16.0 N/cm	■ PP (after 14 days)	24.5 N/cm
■ PVC (initial)	14.0 N/cm	■ PVC (after 14 days)	22.5 N/cm

### Properties

■ Temperature resistance short term	60 °C	■ Static shear resistance at 23°C	++
■ Temperature resistance long term	40 °C	■ Static shear resistance at 40°C	++
■ Tack	++	■ Static shear resistance at 70°C	-
■ Ageing resistance (UV)	o	■ Fogging	++
■ Humidity resistance	+		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=04934>

Page 1 of 1 / As of 06/16/13